

**Amendments to the Claims:**

Claims 1, 7-9, 12, 15, 21 and 23 have been amended herein. Please note that all claims currently pending and under consideration in the referenced application are shown below. Please enter these claims as amended. This listing of claims will replace all prior versions and listings of claims in the application.

**Listing of Claims:**

1. (Currently Amended) An underwater imaging system, comprising:  
an acoustic source configured to generate an acoustic wavefront for impinging upon a target object;  
a first screen having first and second sides, said first side configured to receive a reflected acoustic wavefront as reflected from said target object, said first and second sides further configured to physically deform in response to said reflected acoustic wavefront, said first screen further comprising a pressure compensating layer internally adjacent to said first side to neutralize underwater pressure against said first screen; and  
a first optical processing system optically coupled to said second side of said first screen for converting said reflected acoustic wavefront on said second side of said first screen to a first optical intensity image of said target object.
2. (Original) The system of claim 1, further comprising an acoustic lens arranged between said target object and said first screen and further configured to acoustically process said reflected acoustic wavefront.
3. (Original) The system of claim 1, wherein said first screen is further configured to partition said system into a wet side and a dry side and wherein said optical processing system is arranged on said dry side.

4. (Original) The system of claim 3, further comprising an acoustic lens arranged on said wet side between said target object and said first screen.

5. (Original) The system of claim 1, wherein said first screen is configured as a monolithic screen to directly physically deform from said first side to said second side.

6. (Original) The system of claim 2, wherein said first screen and said acoustic lens are integral and said first screen is formed as a facet of said acoustic lens.

7. (Currently Amended) An underwater imaging system, comprising:  
an acoustic source configured to generate an acoustic wavefront for impinging upon a target  
object;  
a first screen having first and second sides, said first side configured to receive a reflected  
acoustic wavefront as reflected from said target object, said first and second sides further  
configured to physically deform in response to said reflected acoustic wavefront; and  
a first optical processing system optically coupled to said second side of said first screen for  
converting said reflected acoustic wavefront on said second side of said first screen to a  
first optical intensity image of said target object, The system of claim 1,  
wherein said first screen comprises:  
an imaging screen configured to receive a reflected wavefront and physically deform in  
response thereto;  
a pressure compensating layer internally adjacent to said imaging screen and configured  
to neutralize underwater pressure against said imaging screen; and  
a rigid backplane adjacently coupled to said pressure compensating layer and further  
configured for coupling with said first optical processing system.

8. (Currently Amended) ~~An underwater imaging system, comprising:~~  
~~an acoustic source configured to generate an acoustic wavefront for impinging upon a target~~  
~~object;~~  
~~a first screen having first and second sides, said first side configured to receive a reflected~~  
~~acoustic wavefront as reflected from said target object, said first and second sides further~~  
~~configured to physically deform in response to said reflected acoustic wavefront;~~  
~~a first optical processing system optically coupled to said second side of said first screen for~~  
~~converting said reflected acoustic wavefront on said second side of said first screen to a~~  
~~first optical intensity image of said target object; and The system of claim 1, further~~  
~~comprising~~  
a second screen and a second optical processing system configured to generate a second optical  
intensity image of said target object, said second screen and second optical processing  
system spatially separated from said first screen and said first optical processing system to  
form a stereophonic optical image of said target object.

9. (Currently Amended) A method for imaging underwater objects comprising:  
ensonifying a target object with an acoustic wavefront;  
deforming a first side of a first screen and a second side of said first screen in response thereto  
with a reflected acoustic wavefront as reflected by said target object;  
~~pressure compensating said first screen with a pressure compensating layer internally adjacent to~~  
~~said first screen to neutralize underwater pressure against said first screen; and~~  
converting said reflected acoustic wavefront on said second side of said first screen into a first  
optical intensity image of said target object.

10. (Original) The method of claim 9, wherein said converting comprises:  
modulating a reference wavefront with deformations on said second side of said first screen;  
combining in a sensing medium an object wavefront with said reference wavefront as modulated;  
and  
generating a first optical intensity image of said target object as combined in said sensing medium.

11. (Original) The method of claim 9, wherein said converting comprises:  
projecting an optical wavefront on said second side of said first screen; and  
generating a first optical intensity image of said target object from modulation of said first optical wavefront induced by deformations of said first screen from said reflected acoustic wavefront.

12. (Currently Amended) A method for imaging underwater objects comprising:  
ensonifying a target object with an acoustic wavefront;  
deforming a first side of a first screen and a second side of said first screen in response thereto  
with a reflected acoustic wavefront as reflected by said target object;  
converting said reflected acoustic wavefront on said second side of said first screen into a first  
optical intensity image of said target object; ~~The method of claim 9, further comprising:~~  
deforming a first side of a second screen and a second side of said second screen in response  
thereto with a reflected acoustic wavefront as reflected by said target object; and  
converting said reflected acoustic wavefront on said second side of said second screen into a  
second optical intensity image of said target object, said first and second optical intensity  
image forming a stereophonic optical intensity image of said target object.

13. (Original) The method of claim 9, further comprising acoustically modifying said reflected acoustic wavefront between said target object and said first screen through an acoustic lens.

14. (Original) The method of claim 9, further comprising acoustically modifying said reflected acoustic wavefront between said target object and said first screen through an acoustic lens, said first screen and said acoustic lens being integrally arranged.

15. (Currently Amended) An underwater camera, comprising:  
a first screen having first and second sides, said first side configured to receive a reflected acoustic wavefront as reflected from a target object, said first and second sides further configured to physically deform in response to said reflected acoustic wavefront; ~~and~~  
a first optical processing system optically coupled to said second side of said first screen for converting said reflected acoustic wavefront on said second side of said first screen to a first optical intensity image of said target object;  
a housing configured to submersibly enclose said second side of said first screen and said first optical processing system; and  
wherein said first screen further comprises a pressure compensating layer internally adjacent to said first side to neutralize underwater pressure against said first screen.

16. (Original) The underwater camera of claim 15, wherein said first screen further partitions said underwater camera into a wet side on said first side of said first screen and a dry side on said second side of said first screen, said first optical processing system located within said dry side.

17. (Original) The underwater camera of claim 15, further comprising an acoustic lens arranged between said target object and said first screen and further configured to acoustically process said reflected acoustic wavefront.

18. (Original) The underwater camera of claim 17, wherein said first screen and said acoustic lens are integral, said first screen being a facet of said acoustic lens.

19. (Original) The underwater camera of claim 15, further comprising an acoustic source configured to generate an acoustic wavefront for impinging upon a target object.

20. (Original) The underwater camera of claim 15, wherein said first screen is configured as a monolithic screen to directly physically deform from said first side to said second side.

21. (Currently Amended) An underwater camera, comprising:  
a first screen having first and second sides, said first side configured to receive a reflected  
acoustic wavefront as reflected from a target object, said first and second sides further  
configured to physically deform in response to said reflected acoustic wavefront;  
a first optical processing system optically coupled to said second side of said first screen for  
converting said reflected acoustic wavefront on said second side of said first screen to a  
first optical intensity image of said target object; and ~~The underwater camera of claim 15;~~  
wherein said first screen comprises:

an imaging screen configured to receive a reflected wavefront and physically deform in response thereto;

a pressure compensating layer internally adjacent to said imaging screen and configured to neutralize underwater pressure against said imaging screen; and

a rigid backplane adjacently coupled to said pressure compensating layer and further configured for coupling with said first optical processing system.

22. (Original) The underwater camera of claim 15, wherein said first screen is contoured on said second side to optically reflect an object beam of said first optical processing system.

23. (Currently Amended) An underwater camera, comprising:  
a first screen having first and second sides, said first side configured to receive a reflected  
acoustic wavefront as reflected from a target object, said first and second sides further  
configured to physically deform in response to said reflected acoustic wavefront;  
a first optical processing system optically coupled to said second side of said first screen for  
converting said reflected acoustic wavefront on said second side of said first screen to a  
first optical intensity image of said target object; and ~~The underwater camera of claim 15;~~  
~~further comprising~~  
a second screen and a second optical processing system configured to generate a second optical  
intensity image of said target object, said second screen and second optical processing  
system spatially separated from said first screen and said first optical processing system to  
form a stereophonic optical image of said target object.